

Yale® Narrow Aisle Lift Trucks have the ergonomic comfort and the specifications you need. Yale designs and builds narrow aisle trucks that are industry and application specific. Drive motors are application proven for efficiency, performance, and reliability. Yale® Hi-Vis™ masts incorporate innovative engineering for unsurpassed visibility and solid construction.









NR/NDR030-040DA NR/NDR030-045EA

OS030EC

OS/SS030BE

NTA030-035SB

GENERAL	Туре			Single Reach	Double Reach	High Lift Single Reach	High Lift Double Reach	Order Selector	Order Selector	Straddle Selector	Very Narrow
	Yale model designation			NR035-040DA	NDR030DA	NR035-045EA	NDR030-035EA	OS030EC	OS030BE	SS030BE	NTA030-035SB
	Capacity range lbs.			3500-4000	3000	3500-4500	3000-3500	3000	3000	3000	3000-3500
	Power Steering			Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Yale Hi-Vis™ mast			Standard	Standard	Standard	Standard	Standard	Standard	Standard	_
DIMENSIONS	Length to face of forks in		in.	52.12-54.12	58.02-60.02	52.12-62.59	58.02-68.50	72.03-73.03	74.0-75.3	98.5	135.6-159.0
	Chassis width in.		in.	42.8	42.8	42.8	42.8	40	40	40	48-69
	Height in.		in.	87-119	87-119	87-179	87-179	89-105	89.4-119	89.4-131	118.1
	Right angle turn in.			85-96	90-101	85-102	90-105	_	_	_	_
	Mast maximum fork height	Simplex	in.	_	_	_	_	165	_	_	525.2
		Triplex	in.	272	272	422	422	240	276	300	527.6
		Quadplex	in.	_	_	_	_	_	_	_	668
DRIVE	Drive control			AC	AC	AC	AC	SEM Transistor	SEM Transistor	SEM Transistor	AC
	Voltage			24-36	24-36	36	36	24	24-36	24-36	48-72
	Maximum travel speed-mph-empty			6.7	6.7	7.4-8.0	7.4-8.0	6.0	6.0-6.5	5.3-7.5	6.5